


X-board

Movable and intelligent large-size (156") LED products

- > Ultra-light and ultra-thin (thickness of 35mm)
- > Seamless connection of mobile and super large standard 156-inch screen
- > Cell phone APP control and supporting multiple interface signal inputs
- > Magnetic suction module and front maintenance design



SPECIFICATIONS

Parameters	X-board	
Pixel Pitch (mm)	2.571 mm (SMD 2020)	1.8 mm (SMD 1515)
Module Resolution (dots)	112 x 84 dots	160 x 120 dots
Module Size (mm)	288 x 216 mm (11.3"x8.5")	288 x 216 mm (11.3"x8.5")
Pixel Density (dots/m ²)	151,238 dots/m ²	308,642 dots/m ²
Panel Dimension(WxHxD mm) / (Without base)	3456 x 1944 x 35 mm (156")	3456 x 1944 x 35 mm (156")
Panel Material	Aluminum / 7 Colors Optional	Aluminum / 7 Colors Optional
Panel Weight (kg/panel)	155 kg/panel (341.7 lb/panel)	155 kg/panel (341.7 lb/panel)
Color Depth (Bit)	14 bit	14 bit
Refresh Rate (Hz)	≥3600 Hz	≥3600 Hz
Driver Method / scan	Scan 1/28	Scan 1/30
Brightness (nits)	≥1000 nits	600 ~ 800 nits, adjustable
Viewing Angle (H°/V°)	160° / 160°	160° / 160°
Display Resolution (WxH) / (pixel)	1344 x 756 pixel	1920 x 1080 pixel
Connection Type	USB / HDMI / WIFI / Internet	USB / HDMI / WIFI / Internet
Supported Video Files	MP4, AVI, WMV and more	MP4, AVI, WMV and more
AC Power Input (V)	AC110V~ 220V ±10%	AC110V~ 220V ±10%
AC Power Frequency (Hz)	50 ~ 60 Hz	50 ~ 60 Hz
Max. / Avg. Power (W/m ²)	660 W/m ² / 200 W/m ²	660 W/m ² / 200 W/m ²
Operating Temperature (°C)	-10°C ~ 50°C	-10°C ~ 50°C

Dexterous, light and thin, and concise
X-board (Indoor Mobile)