


X-poster

Stylish vanguard LED products (80")

- > The thinnest LED commercial display (35mm thick) in the whole world
- > Cell phone APP control and supporting application in various occasions
- > Movable, supporting multiple interface signal inputs
- > Magnetic suction module and front maintenance design



SPECIFICATIONS

Parameters	X-poster	
Pixel Pitch (mm)	1.8 mm (SMD 1515)	2.571 mm (SMD 2020)
Module Resolution (dots)	160 x 120 dots	112 x 84 dots
Module Size (mm)	288 x 216 mm (11.3"x8.5")	288 x 216 mm (11.3"x8.5")
Pixel Density (dots/m ²)	308,642 dots/m ²	151,238 dots/m ²
Panel Dimension(WxHxD) / (mm)	576 x 1944 x 35 mm (22.7"x76.5"x1.4")	576 x 1944 x 35 mm (22.7"x76.5"x1.4")
Panel Material	Aluminum / 7 Colors Optional	Aluminum / 7 Colors Optional
Panel Weight (kg/panel)	35 kg/panel (77.2 lb/panel)	35 kg/panel (77.2 lb/panel)
Color Depth (Bit)	14 bit	14 bit
Refresh Rate (Hz)	≥3600 Hz	≥3600 Hz
Driver Method / scan	Scan 1/30	Scan 1/28
Brightness (nits)	600 ~ 800 nits, adjustable	≥1000 nits
Viewing Angle (H° / V°)	160 ° / 160 °	160 ° / 160 °
Display Resolution (WxH) / (pixel)	320 x 1080 pixel	224 x 756 pixel
Connection Type	USB / HDMI / WIFI / Internet	USB / HDMI / WIFI / Internet
Supported Video Files	MP4, AVI, WMV and more	MP4, AVI, WMV and more
AC Power Input (V)	AC110V~ 220V ±10%	AC110V~ 220V ±10%
AC Power Frequency (Hz)	50 ~ 60 Hz	50 ~ 60 Hz
Max. / Avg. Power (W/m ²)	660 W/m ² / 200 W/m ²	660 W/m ² / 200 W/m ²
Operating Temperature (C)	-10 C ~ 50 C	-10 C ~ 50 C

Stylish, vanguard and ultra-thin
X-poster (Indoor Mobile)