High Brightness Display



Store Window Displays

Digital media is only effective if viewers are able to see it. Zoom Digital Signage high bright professional LCDs are a perfect solution for indoor environments that receive a high amount of ambient light such as storefront windows. To prevent blackening defect, ZDS offers High-Tni liquid crystal panels which can withstand temperatures up to 110°C (230°F). A fanless thermal management system provides silent, trouble-free operation.

Suggested Uses

- Retail stores
- Theater
- Banks
- Travel agencies
- Real Estate Offices
- Post Offices

specifications

		ZI46EH	Z146	ZI55	Z175
Size		46"	46"	55"	75"
Number of Pixels		1920x1080	1920x1080	1920 x 1080	1920 x 1080
Brightness (typ)		5,000nit	2,500nit	2,500nit	2,500nit
Pixel Arrangement		RGB Vertical stripe	RGB Vertical stripe	RGB Vertical stripe	RGB Vertical stripe
Aspect Ratio		16:9	16:9	16:9	16:9
Viewing Angle		178°	178°	178°	178°
Lifetime		N/A	45,000+ hours	45,000+ hours	45,000+ hours
Backlight		Direct LED	Direct LED	Direct LED	Direct LED
Display Area		1018.08mm(H) x 572.67mm(V)	1018.08mm(H) x 572.67mm(V)	1209.6mm(H) x 680.4mm(V)	1650.24mm(H) x 928.26mm(V)
Display colors		16.7M (8bit)	16.7M (8bit)	16.7M (8bit)	16.7M (8bit)
Surface treatment		Haze 0%	Haze 0%	Haze 0%	Haze 0%
Driver Element		a-Si TFT active matrix	a-Si TFT active matrix	a-Si TFT active matrix	a-Si TFT active matrix
Inputs	HDMI	1	1	1	1
	DVI	1	1	1	1
	RGB	1	1	1	1
	AUDIO	1	1	1	1
	RS-232	Optional	Optional	Optional	Optional
Display Mode		Normally Black	Normally Black	Normally Black	Normally Black

The ZDS Display Difference



High Quality Display 46", 55" or 75" with 2,500 nit



Number of Pixels 1920 x 1080(WUXGA), 1080p



Panel Technology LED BACKLIT LCD



Available narrow bezel for video wall applications



Low Voltage Differential Signaling interface (2 Pixel / Clock)



High Tni((110°C) Liquid Crystal



Sunlight Viewable



Amazing feature resulting in a high contrast picture



Wide Viewing Angle (H/W) 178° / 178°



Longer Life Time 45,000 hrs (2x standard life)